


V-FLOW TYPE GT

Rigid and compact filters



APPLICATIONS

- Used in gas turbine
- Terminal filtration in air treatment units

GENERAL FEATURES

- Efficiency EN779: M6-F9
- Media: Mini pleat fiberglass paper
- Frame: Plastic
- Sealant: Polyurethane
- Separator: Hot-melt beads
- Final pressure drop: 600 Pa
- Maximum T° in continuous service: 70°C
- Humidity: 100% RH

ADVANTAGES

- Compact and economic
- High filtration area
- High efficiency
- Tested for food contact according to CE 1935/2004
- Certified for microbial development (ISO 846-VD 6022)

Grade	Width A (mm)	Height B (mm)	Depth C (mm)	Media Area (m ²)	Flow Rate (m ³ /h)/ Delta P (Pa)	Energy cons. (Kwh/an) *	Energy class **
M6	592	592	440	32	3400/ 65	806	C
M6	592	490	440	27	3500/ 65	-	
M6	592	287	440	16	2125/ 65	-	
F7	592	592	440	32	3400/ 72	871	A
F7	592	490	440	27	3500/ 72	-	
F7	592	287	440	16	2125 / 72	-	
F8	592	592	440	32	3400/ 78	946	A
F8	592	490	440	27	3500/ 78	-	
F8	592	287	440	16	2125/ 78	-	
F9	592	592	440	32	3400/ 97	1170	A
F9	592	490	440	27	3500/ 97	-	
F9	592	287	440	16	2125/ 97	-	

* Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2018

** Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2019



FILTREX