

# HYDROPHOBIC PLEATED PANEL FILTER

WHITE PLEATED PANEL, GRADE G4



## SPECIFICATIONS

- Disposable pleated pre-filter for HVAC applications
- Hydrophobic media will not absorb moisture in the air
- Moisture resistant card frame
- Efficiency grade: G4

Product Group				B301		B302		B303	
Nominal Depth C (inch)				1		2		4	
Actual Depth C (mm)				20		50		100	
Height A		Width B		Flow Rate	Initial Pressure Drop	Flow Rate	Initial Pressure Drop	Flow Rate	Initial Pressure Drop
mm	Inch	mm	Inch	(m3/h)	(pa)	(m3/h)	(pa)	(m3/h)	(pa)
241	10	241	10	314	49	525	65	560	61
292	12	292	12	460	49	770	65	820	61
368	15	368	15	731	49	1220	65	1305	61
394	16	394	16	838	49	1400	65	1495	61
445	18	445	18	1069	49	1785	65	1905	61
495	20	241	10	644	49	1075	65	1150	61
495	20	368	15	984	49	1640	65	1755	61
495	20	394	16	1053	49	1760	65	1880	61
495	20	495	20	1323	49	2210	65	2360	61
594	24	292	12	937	49	1565	65	1670	61
594	24	495	20	1588	49	2650	65	2830	61
594	24	594	24	1905	49	3180	65	3400	61
622	25	622	16	1323	49	2210	65	2360	61
622	25	495	20	1663	49	2775	65	2965	61



**FILTREX**

SMART FILTRATION