

F900 HIGH EFFICIENCY MICROPLEAT

METAL/CARD FRAMED MICROPLEAT FILTER



SPECIFICATIONS

- Compact and Economic
- High Filtration Area
- Efficiency EN779: F7-F8
- Final Pressure Drop: 195-238Pa
- Maximum To in continuous service: 100oC
- Humidity: 100% RH

Product Code		Height A		Width B		Depth C		Filter Class	Flow Rate (m ³ /hr)	Pressure Drop (Pa)	
Card	Metal	Nominal (inch)	mm	Nominal (inch)	mm	Nominal (inch)	mm			Initial	Final
F900/1233	F900/1005	24	594	12	292	2	45	F7	1250	95	195
F900/1232	F900/1015	24	594	20	495	2	45	F7	2115	95	195
F900/1231	F900/1021	24	594	24	594	2	45	F7	2540	95	195
F900/1295	F900/1296	24	594	12	292	2	45	F8	1250	138	238
F900/1272	F900/1265	24	594	20	495	2	45	F8	2115	138	238
F900/1273	F900/1086	24	594	24	594	2	45	F8	2540	138	238
F900/1230	F900/1128	24	594	12	292	4	95	F7	1415	105	205
F900/1206	F900/1125	24	594	20	495	4	95	F7	2405	105	205
F900/1205	F900/1087	24	594	24	594	4	95	F7	2885	105	205
F900/1217	F900/1112	24	594	12	292	4	95	F8	1415	129	229
F900/1256	F900/1297	24	594	20	495	4	95	F8	2405	129	229
F900/1218	F900/1032	24	594	24	594	4	95	F8	2885	129	229



FILTREX

SMART FILTRATION