

F97./F98. HIGH EFFICIENCY MICROPLEAT

METAL/CARD FRAMED MICROPLEAT FILTER



F971/F981
(metal frame)



F972/F982
(card frame)

SPECIFICATIONS

- Compact and Economic
- High Filtration Area
- Efficiency EN779: F7-F8
- Final Pressure Drop: 195-238Pa
- Maximum Temp. in continuous service: 100°C
- Humidity: 100% RH

Product Code		Height A		Width B		Depth C		Filter Class	Flow Rate (m ³ /hr)	Pressure Drop (Pa)	
Card	Metal	Nominal (inch)	mm	Nominal (inch)	mm	Nominal (inch)	mm			Initial	Final
F972/2001	F971/2001	24	594	12	292	2	45	F7	1250	95	195
F972/2002	F971/2027	24	594	20	495	2	45	F7	2115	95	195
F972/2000	F971/2028	24	594	24	594	2	45	F7	2540	95	195
F982/2000	F981/2000	24	594	12	292	2	45	F8	1250	138	238
F982/2008	F981/2003	24	594	20	495	2	45	F8	2115	138	238
F982/2007	F981/2006	24	594	24	594	2	45	F8	2540	138	238
F972/4001	F971/4012	24	594	12	292	4	95	F7	1415	105	205
F972/4006	F971/4013	24	594	20	495	4	95	F7	2405	105	205
F972/4007	F971/4018	24	594	24	594	4	95	F7	2885	105	205
F982/4002	F981/4007	24	594	12	292	4	95	F8	1415	129	229
F982/4001	F981/4000	24	594	20	495	4	95	F8	2405	129	229
F982/4003	F981/4008	24	594	24	594	4	95	F8	2885	129	229



FILTREX

SMART FILTRATION